INFORME DATOS **TÉCNICOS**

THE MANUFACTURER

S.A.C.I.D.
Raval dels Torrents, Par. 4 DC-163
08297 CASTELLGALÍ
BARCELONA (ESPAÑA)

INFORMS THAT THE FOLLOWING PPE :

KORDA'S - LLUISA 10,5

FOLLOWING THE STANDART	EN1891	**SEMI-ESTATIC ROPE TYPE A**
	EN892	**DYNAMIC SIMPLE ROPE**
CERTIFICATE NUMBERS	0082/483/160/01/24/0013	

SATISFIES THE DISPOSITIONS OF THE REGULATION UE2016-425,
WITH THE FOLLOWING TECHNICAL DATA OF CERTIFICATION:

EN1891 Type A	
Diameter	10,6 mm
Weight per meter	77,0 g/m
Core Weight	48,1 g/m
Core Percentage	62,5%
Sheath Weight	28,9 g/m
Sheath Percentage	37,5%
Knotability	1,1
Sheath Slippage	0%
Elongation	4,1%
Impact Force (F0,3) (knot 8)	4,4 kN
Impact Force (F0,3) (sewing)	4,6 kN
Number of Falls (F1) (knot 8)	>5
Number of Falls (F1) (sewing)	>5
Static Resistance	32,3 kN
Resistance with 8-knot	3min 15 kN
Material	POLIAMIDA
Melting Temperature	216 °C
Shrinkage	-0,2%

(*) Instead of shrinking, it stretches

EN 892 Simple rope	
Diameter	10,6 mm
Weight per meter	77,0 g/m
Core Percentage	62,5%
Sheath Slippage	0 mm
Elongation	3,1%
Impact Force (F2)	10,3 kN
Number of Falls (F2)	8
Dynamic Elasticity	24,0%

ISSUED IN: CASTELLGALÍ

DATED: 20/10/2026

Technical Department
KORDA'S