

**THE MANUFACTURER:**

**S.A.C.I.D.**

Raval dels Torrents, Par. 4 DC-163  
08297 CASTELLGALÍ  
BARCELONA (SPAIN)

**INFORMS THAT THE FOLLOWING PPE :**

**KORDA'S - STARK 10,5**

NORM WHICH MEETS: **EN1891:1998**  
**SEMIESTATIC ROPE TYPE A**

N. CERTIFICATION: **0082/483/160/05/22/0310**

**SATISFIES THE DISPOSITIONS OF THE REGULATION UE2016-425,  
WITH THE FOLLOWING TECHNICAL DATA OF CERTIFICATION:**

|                               |            |
|-------------------------------|------------|
| Diameter                      | 10,5 mm    |
| Weight per meter              | 71 g/m     |
| Core Weight                   | 40,5 g/m   |
| Core Percentage               | 57%        |
| Sheath Weight                 | 30,5 g/m   |
| Sheath Percentage             | 43%        |
| Flexibility                   | 1,07       |
| Sheath Slippage               | 0,0%       |
| Elongation                    | 3,6%       |
| Impact Force (F0,3) (knot 8)  | 5,1 kN     |
| Impact Force (F0,3) (sewing)  | 5,3 kN     |
| Number of Falls (F1) (knot 8) | >5         |
| Number of Falls (F1) (sewing) | >5         |
| Material                      | POLYAMIDE  |
| Melting Temperature           | 216 °C     |
| Shrinkage                     | -0,1 % (*) |
| Resistance with 8-knot        | 3min 15 kN |
| Resistance with sewing        | 3min 15 kN |
| Static Resistance             | 30 kN      |

(\*) Instead of shrinking it elonges 0,1 %

ISSUED IN: CASTELLGALÍ

DATE: 08/10/2026

Technique Department  
KORDA'S